



Closed Loop Cooling Center / Engine Dynamometer



200 hp (149 kW) shown here
(product may differ)

Dyne Systems has a family of Closed Loop Cooling Centers (CLCC), each sized to handle the heat rejection typically required for engines that are of 200 hp, 500 hp, 800 hp, 1,250 hp and 2,500 hp (149 kW, 373 kW, 597 kW, 932 kW and 1,864 kW). The CLCC allows you to use a glycol-based coolant to regulate an engine coolant circuit temperature while cooling the CLCC with the facility process water.

The CLCC system utilizes a heat exchanger (liquid-to-liquid) and temperature sensor to control and monitor the coolant temperature. The coolant temperature is controlled by a set point that you set in the controller or remotely using a remote set point from the DynPro₂ Data Acquisition and Control System. All you need is an optional DynPro₂ cable to enable this capability. The CLCC also includes a coolant pump within the enclosure. This coolant pump is used to fill and empty the engine before and after testing. A coolant tank of suitable capacity is required to complete the system and an expansion tank is required to capture gasses entrained in the coolant and allow for fluid expansion.

Everything you need to succeed



Dyne Systems is a division of Taylor Dynamometer
W209 N17391 Industrial Dr., Jackson, WI 53037
(800) 657-0726 www.dynesystems.com

DS2708v001